

1600 Liquid Adhesive

1600 is a high strength liquid adhesive that can be applied by spray nozzle, brush, or roller. It forms an excellent bond between acoustical foam and a variety of substrates (wood, metal, plastics, etc.) It is non-flammable and fast setting.

PRODUCT DATA:

PROPERTIES:

- **Flammability:** Non-Flammable
- **Color:** Clear, Red
- **Odor:** Characteristic of chlorinated solvent
- **Flash Point:** None
- **Solvent:** Methylene Chloride and Mineral Spirits
- **Viscosity:** 400-500 cps. (model RVF Brookfield)
#3 spindle 10 rpm @ 78° F.
- **Weight per gallon:** 9.5 + .1 lbs.
- **Weight solids:** 32%
- **Volume solids:** 38%
- **Coverage:** 600 sq. ft./gallon/mil thickness
- **Bonding Range:** From 30 seconds to 5 minutes, depending on application, temperature, and humidity.
- **Temperature resistance:** -20° F. to 210° F.
- **T.L.V. (P.P.M.):** 500

CHARACTERISTICS:

- Fast setting - Apply to both surfaces, let set 5-10 min., and then put the two together.
- Excellent water resistance
- Non-Flammable
- Designed for R.V. Conversion, Foam Fabrication, R.V. Seat Assembly and Marine Carpet Application.

APPLICATION:

Apply by spray, brush, or roller. Binks Gun - Model #62 or 2001-63B Fluid Nozzle-66 PJ Air Cap. For clean up use Lacquer Thinner.

STORAGE:

Shelf life 1 year in closed container. Store in cool area